

ComputeCosts observatory report 002

arXiv archive, epoch 1

Mateo Mayer

21 February 2026

Abstract

This report documents the first structural analysis of the arXiv archive within the ComputeCosts observatory. The archive records metadata and abstracts of recently published scientific papers and treats this collection as a measurable signal of how computational infrastructure is described in scientific writing.

The dataset analysed in this report contains 6690 unique papers obtained through a deterministic ingestion pipeline. The epoch 1 observation period spans from 1 January 2025 00:00 UTC until 19 February 2026, corresponding to the ingestion state frozen at the time of this report. The analysis deliberately collapses the entire dataset into a single baseline snapshot rather than attempting to interpret short term variation. The objective is not to measure trends but to determine whether the archive contains measurable signals relating to cloud infrastructure, local computation and operational constraints.

Initial measurements show that abstracts already contain operationally relevant signals, even though detailed deployment narratives are not typically expected in scientific papers. Mentions of self hosted and local execution vocabulary indicate that local compute set ups are explicitly used in a measurable subset of the dataset. Hardware references to consumer GPUs, specifically NVIDIA RTX class devices including RTX 4090, demonstrate that workstation grade hardware is used for scientific computing in published research.

These observations are particularly valuable because the archive is accompanied by a complete local PDF collection for the full dataset. The present report does not analyse those PDFs, but their availability means that the abstract level signals identified here can be deepened later through full text extraction, context reconstruction and evidence snippets. The abstract results therefore function as a calibration step that justifies a second phase of deeper paper level analysis.

Scope and positioning

This is an independent observatory report. It is not peer reviewed.

The purpose of the report is to document the first deterministic measurement of the arXiv archive of the ComputeCosts observatory and to provide a transparent baseline from which later analyses can evolve. The report therefore prioritises reproducibility and auditability over interpretive claims.

The archive is designed as a forward looking sensor that records how infrastructure related concepts appear in scientific communication. It does not attempt to measure adoption rates of

cloud or local systems. Instead it records the vocabulary used by researchers when describing computational work.

As with the other archives of the observatory, the dataset state is anchored on the Algorand blockchain. The anchoring mechanism commits hashes of the JSONL records as transaction notes so that the integrity of the dataset can later be independently verified. The anchor asset and its transaction history are publicly inspectable at

<https://explorer.perawallet.app/asset/3455286633/>.

Dataset

The dataset used in this report consists of a JSONL archive containing metadata and abstracts of arXiv submissions collected through the ComputeCosts ingestion pipeline. The specific file analysed in this report contains 6690 rows corresponding to 6690 unique arXiv identifiers.

Canonicalisation confirms that the dataset contains no duplicates under the defined rule of one record per arXiv identifier. The internal consistency of the dataset therefore indicates that the export process produced a clean snapshot suitable for baseline analysis.

Each record contains publication timestamps, authorship metadata, the abstract text and the query that originally surfaced the paper during ingestion. Because abstracts summarise the methods and computational setup used in research projects, they provide a compact textual signal of how compute infrastructure is described within scientific literature.

It is important to emphasise that the dataset does not measure where workloads actually run. Instead it captures the language researchers use when presenting their work. The archive should therefore be interpreted as a linguistic observation of the research ecosystem rather than an operational measurement.

Method

The analysis follows the same principle used throughout the observatory: collapse the entire epoch into a single stable snapshot and extract deterministic signals from that snapshot. The objective is not to infer trends but to determine whether the archive contains measurable structure under a fixed vocabulary.

All abstracts and titles are normalised and scanned for a predefined set of phrases representing infrastructure concepts, deployment patterns, cost related constraints and hardware configurations. Each phrase group defines a measurement dimension such as cloud computing references, local inference, billing terminology or consumer GPU hardware mentions.

For each dimension the number of papers containing at least one occurrence of the phrase is counted and expressed as a share of the entire dataset. A second calculation measures whether certain concepts appear together in the same abstract, producing a simple co occurrence signal. These counts provide a minimal but reproducible representation of how infrastructure related language appears across the archive.

Results

The baseline snapshot derived from the JSONL archive reveals several structural properties of the dataset. Privacy related terminology appears in 5984 of the 6690 papers, corresponding to approximately 0.8945 of the dataset. This extremely high prevalence indicates that privacy language forms a dominant component of contemporary research abstracts within the collected slice of arXiv.

Explicit references to cloud computing appear in 253 papers, representing roughly 0.0378 of the dataset. Hardware references to consumer graphics cards appear in a smaller but still measurable number of papers, with 59 mentions of RTX 4090 hardware and an equal number of references to NVIDIA RTX devices more generally.

Operational constraint vocabulary appears rarely. Billing terminology appears in 49 papers, quota related language in 46 papers and vendor lock in discussions in 19 papers. References to self hosted deployment, local large language models and running systems locally appear in only a small fraction of abstracts.

Co occurrence measurements reinforce this picture. Only nine papers contain both self hosted terminology and privacy related language, while combinations involving cloud GPU constraints appear extremely rarely in the dataset. The archive therefore suggests that operational discussions of infrastructure constraints are not commonly included in scientific abstracts.

Although the absolute shares of local deployment and consumer GPU terms are small, their presence in abstracts is a strong indicator that these practices are sufficiently central to be reported even in compressed scientific summaries. In other words, the signal is likely conservative. If a practice appears in the abstract, it is generally not a marginal detail. The RTX class hardware references are therefore an especially informative early indicator of workstation level scientific computing activity.

Critical analysis

Although the dataset produces clear numerical signals, their interpretation requires caution. Abstracts are designed to summarise scientific contributions rather than operational details. Researchers often describe algorithms, datasets and evaluation methods while omitting practical aspects of the computing environment. This implies that abstract based infrastructure measurements are conservative by design: the absence of a term does not imply absence of a practice.

At the same time, the presence of local deployment language and consumer GPU hardware references in abstracts is therefore particularly informative. It suggests that these elements are not merely incidental implementation details but are sufficiently important to be included in the most compressed representation of the work. This strengthens the rationale for a second phase analysis based on full paper PDFs, where compute environment details, limitations and practical constraints are more likely to appear.

The extremely high frequency of privacy related terminology illustrates another limitation. Within machine learning research the term privacy frequently refers to algorithmic frameworks such as

differential privacy or privacy preserving training rather than infrastructure level concerns. The current measurement therefore aggregates several distinct meanings under a single word.

These limitations do not invalidate the dataset but they do shape its interpretation. The archive measures how infrastructure concepts appear in the language of scientific writing, not necessarily how systems are deployed in practice. When combined with observations from developer platforms and operational discussions, however, this linguistic signal can help reveal broader patterns in the compute ecosystem.

Conclusion

The first baseline analysis of the arXiv archive shows that the dataset contains measurable signals related to infrastructure vocabulary, hardware references and operational terminology. The abstract level signals identified in this report justify deeper full text analysis of the archived PDFs in a subsequent report, because the presence of these signals in abstracts indicates that additional operational detail is likely recoverable from the full papers.

Privacy related language dominates the dataset, while explicit references to cloud infrastructure, local deployment and operational constraints appear far less frequently.

Because abstracts focus on scientific contributions rather than system administration, the archive should be interpreted as a linguistic sensor of the research community. Its primary value lies in providing a reproducible dataset that can be analysed repeatedly and compared with signals from other technical environments within the broader ComputeCosts observatory.

Appendix A, Key numeric outputs and python program listing

Total rows analysed, 6690.

Unique arXiv identifiers, 6690.

Duplicates detected, 0.

Privacy mentions, 5984 papers.

Cloud computing mentions, 253 papers.

RTX 4090 mentions, 59 papers.

NVIDIA RTX mentions, 59 papers.

Billing terminology, 49 papers.

Quota terminology, 46 papers.

Self hosted terminology, 29 papers.

Local LLM terminology, 25 papers.

Run locally terminology, 23 papers.

Vendor lock in terminology, 19 papers.

Figures produced with the python program below.

```
#!/usr/bin/env python3
# -*- coding: utf-8 -*-

import csv
import glob
import json
import os
import re
import sys
import unicodedata
from dataclasses import dataclass
from datetime import datetime, timezone
from typing import Any, Dict, List, Optional, Tuple

SCRIPT_VERSION = "epoch1_kiss_1.0"

def _utc_now_iso() -> str:
    return datetime.now(timezone.utc).replace(microsecond=0).isoformat().
        replace("+00:00", "Z")

def _safe_str(x: Any) -> str:
    if x is None:
```

```

return ""
if isinstance(x, str):
return x
return str(x)

def _normalize_text(s: str) -> str:
s = _safe_str(s)
s = unicodedata.normalize("NFKC", s)
s = s.lower()
s = re.sub(r"\s+", " ", s).strip()
return s

_ARXIV_ABS_RE = re.compile(r"(?:arxiv\.org/(?:abs|pdf)/)(\d{4}\.\d{4,5})
(?:v\d+)?", re.IGNORECASE)
_ARXIV_OLD_RE = re.compile(r"(?:arxiv\.org/(?:abs|pdf)/)([a-z\-\-]/\d{7})
(?:v\d+)?", re.IGNORECASE)
_ARXIV_ID_BARE_RE = re.compile(r"^\d{4}\.\d{4,5})(?:v\d+)?$", re.
IGNORECASE)
_ARXIV_OLD_BARE_RE = re.compile(r"^[a-z\-\-]/\d{7})(?:v\d+)?$", re.
IGNORECASE)

def _extract_arxiv_id(raw: Any) -> str:
s = _safe_str(raw).strip()

m = _ARXIV_ABS_RE.search(s)
if m:
return m.group(1)

m = _ARXIV_OLD_RE.search(s)
if m:
return m.group(1)

m = _ARXIV_ID_BARE_RE.match(s)
if m:
return m.group(1)

m = _ARXIV_OLD_BARE_RE.match(s)
if m:
return m.group(1)

if s.startswith("http") and "arxiv.org" in s:
return s

return s

```

```

def _parse_dt_utc(s: Any) -> Optional[datetime]:
    t = _safe_str(s).strip()
    if not t:
        return None

    try:
        if t.endswith("Z"):
            return datetime.fromisoformat(t.replace("Z", "+00:00")).astimezone(
                timezone.utc)
        if "+" in t or t.endswith("00:00") or t.endswith("00:00:00"):
            return datetime.fromisoformat(t).astimezone(timezone.utc)
        return datetime.fromisoformat(t).replace(tzinfo=timezone.utc)
    except Exception:
        pass

    fmts = [
        "%Y-%m-%d %H:%M:%S",
        "%Y-%m-%d %H:%M",
        "%Y-%m-%d",
    ]
    for f in fmts:
        try:
            return datetime.strptime(t, f).replace(tzinfo=timezone.utc)
        except Exception:
            continue

    return None

def _choose_input_jsonl() -> str:
    cwd = os.getcwd()

    preferred = []
    for name in ["arxiv.jsonl", "arxiv_epoch1.jsonl", "arxiv_19022026.jsonl"
        ]:
        p = os.path.join(cwd, name)
        if os.path.isfile(p):
            preferred.append(p)

    candidates = preferred[:]
    candidates.extend(sorted(glob.glob(os.path.join(cwd, "*.jsonl"))))

    if not candidates:
        raise FileNotFoundError("No .jsonl file found in the working directory."
            )

    uniq = []

```

```

seen = set()
for c in candidates:
    if c not in seen:
        seen.add(c)
    uniq.append(c)

def key(p: str) -> Tuple[int, float]:
    base = os.path.basename(p).lower()
    score = 0
    if base == "arxiv.jsonl":
        score = 3
    elif base.startswith("arxiv_"):
        score = 2
    elif "arxiv" in base:
        score = 1
    try:
        mt = os.path.getmtime(p)
    except Exception:
        mt = 0.0
    return (score, mt)

uniq.sort(key=key, reverse=True)
return uniq[0]

def _get_field(rec: Dict[str, Any], keys: List[str]) -> Any:
    for k in keys:
        if k in rec:
            return rec.get(k)
    return None

def _authors_count(rec: Dict[str, Any]) -> int:
    a = _get_field(rec, ["authors", "author", "authors_list"])
    if a is None:
        return 0
    if isinstance(a, list):
        return len(a)
    if isinstance(a, str) and a.strip():
        return len([x for x in a.split(",") if x.strip()])
    return 0

@dataclass
class CanonicalRow:
    arxiv_id: str
    published_utc: str
    updated_utc: str

```

```

primary_category: str
title: str
summary: str
query: str
authors_count: int

def _dimension_config() -> Dict[str, List[str]]:
return {
    "local_llm": ["local llm"],
    "local_llama": ["local llama"],
    "run_locally": ["run locally", "runs locally", "running locally"
    ],
    "self_hosted": ["self hosted", "self-hosted", "selfhosted"],
    "on_prem_gpu": ["on-prem gpu", "on prem gpu", "onprem gpu", "on-
    premise gpu", "on premise gpu", "onpremise gpu"],
    "cloud_gpu": ["cloud gpu"],
    "cloud_computing": ["cloud computing"],
    "cloud_costs": ["cloud costs", "cloud cost"],
    "egress_fees": ["egress fees", "egress fee"],
    "quota": ["quota", "rate limit", "rate-limit", "quota limit", "
    quota limits"],
    "billing": ["billing", "billed", "invoice", "invoicing", "
    billable"],
    "vendor_lock": ["vendor lock in", "vendor lock-in", "vendor
    lockin", "lock-in", "lock in"],
    "privacy": ["privacy", "confidential", "sensitive data", "data
    sovereignty"],
    "offline_inference": ["offline inference", "infer offline", "
    offline infer"],
    "rtx_5090": ["rtx 5090"],
    "rtx_4090": ["rtx 4090"],
    "nvidia_rtx": ["nvidia rtx", "geforce rtx"],
    "ram_128_gb": ["128 gb ram", "128gb ram", "128-gb ram", "128 gb
    memory", "128gb memory", "128-gb memory"],
    "ram_64_gb": ["64 gb ram", "64gb ram", "64-gb ram", "64 gb memory
    ", "64gb memory", "64-gb memory"],
}

def _make_phrase_patterns(cfg: Dict[str, List[str]]) -> Dict[str, List[
    re.Pattern]]:
out: Dict[str, List[re.Pattern]] = {}
for dim, phrases in cfg.items():
    pats = []
    for ph in phrases:
        phn = _normalize_text(ph)
        phn = re.escape(phn)

```

```

pat = re.compile(r"(?:^[^a-z0-9])" + phn + r"(?:$|[^a-z0-9])")
pats.append(pat)
out[dim] = pats
return out

def _count_hits(text_norm: str, pats: List[re.Pattern]) -> int:
    cnt = 0
    for p in pats:
        cnt += len(p.findall(text_norm))
    return cnt

def main() -> int:
    run_ts = _utc_now_iso()

    try:
        input_path = _choose_input_jsonl()
    except Exception as e:
        print(f"error: {e}", file=sys.stderr)
    return 2

total_rows = 0

best_by_id: Dict[str, Dict[str, Any]] = {}
best_updated: Dict[str, datetime] = {}
duplicates = 0

with open(input_path, "r", encoding="utf-8") as f:
    for line in f:
        line = line.strip()
        if not line:
            continue
        total_rows += 1
        try:
            rec = json.loads(line)
        except Exception:
            continue

        raw_id = _get_field(rec, ["arxiv_id", "id", "entry_id", "identifier"])
        arxiv_id = _extract_arxiv_id(raw_id)

        if not arxiv_id:
            continue

        updated_raw = _get_field(rec, ["updated_utc", "updated", "update", "
            last_updated"])
        upd_dt = _parse_dt_utc(updated_raw) or datetime(1970, 1, 1, tzinfo=

```

```

        timezone.utc)

if arxiv_id in best_by_id:
    duplicates += 1
if upd_dt > best_updated.get(arxiv_id, datetime(1970, 1, 1, tzinfo=
    timezone.utc)):
    best_by_id[arxiv_id] = rec
    best_updated[arxiv_id] = upd_dt
else:
    best_by_id[arxiv_id] = rec
    best_updated[arxiv_id] = upd_dt

canonical_rows: List[CanonicalRow] = []
for arxiv_id, rec in best_by_id.items():
    pub_dt = _parse_dt_utc(_get_field(rec, ["published_utc", "published", "
        publish", "created"]))
    upd_dt = _parse_dt_utc(_get_field(rec, ["updated_utc", "updated", "
        update", "last_updated"]))

    published_utc = (pub_dt.astimezone(timezone.utc).replace(microsecond=0).
        isoformat().replace("+00:00", "Z"))
    if pub_dt else ""
    updated_utc = (upd_dt.astimezone(timezone.utc).replace(microsecond=0).
        isoformat().replace("+00:00", "Z"))
    if upd_dt else ""

    primary_category = _safe_str(_get_field(rec, ["primary_category", "
        primaryCategory", "primary_cat"])).strip()

    cats = _get_field(rec, ["categories", "category", "cats"])
    if not primary_category:
        if isinstance(cats, list) and cats:
            primary_category = _safe_str(cats[0]).strip()
        elif isinstance(cats, str) and cats.strip():
            primary_category = cats.strip().split()[0]

    title = _safe_str(_get_field(rec, ["title"])).strip()
    summary = _safe_str(_get_field(rec, ["summary", "abstract"])).strip()

    query = _safe_str(_get_field(rec, ["query", "search_term", "term"])).
        strip()

    canonical_rows.append(
        CanonicalRow(
            arxiv_id=arxiv_id,
            published_utc=published_utc,
            updated_utc=updated_utc,
            primary_category=primary_category,

```

```

title=title,
summary=summary,
query=query,
authors_count=_authors_count(rec),
)
)

canonical_rows.sort(key=lambda r: (r.published_utc or "", r.arxiv_id))

canonical_path = "canonical_papers.csv"
with open(canonical_path, "w", newline="", encoding="utf-8") as f:
w = csv.writer(f)
w.writerow(["arxiv_id", "published_utc", "primary_category", "
    authors_count", "title", "summary", "query"])
for r in canonical_rows:
w.writerow([
r.arxiv_id,
r.published_utc,
r.primary_category,
r.authors_count,
r.title,
r.summary,
r.query,
])

dim_cfg = _dimension_config()
dim_pats = _make_phrase_patterns(dim_cfg)

dim_papers: Dict[str, int] = {k: 0 for k in dim_cfg.keys()}
dim_mentions: Dict[str, int] = {k: 0 for k in dim_cfg.keys()}

pair_list = [
("cloud_gpu", "egress_fees"),
("cloud_gpu", "quota"),
("cloud_gpu", "billing"),
("cloud_gpu", "vendor_lock"),
("cloud_gpu", "privacy"),
("self_hosted", "privacy"),
("local_llm", "offline_inference"),
("on_prem_gpu", "privacy"),
]
pair_counts: Dict[Tuple[str, str], int] = {p: 0 for p in pair_list}

for r in canonical_rows:
text = f"{r.title}\n{r.summary}"
t = _normalize_text(text)

hits: Dict[str, int] = {}

```

```

for dim, pats in dim_pats.items():
    c = _count_hits(t, pats)
    hits[dim] = c
    if c > 0:
        dim_papers[dim] += 1
        dim_mentions[dim] += c

hit_bool = {k: (hits.get(k, 0) > 0) for k in dim_cfg.keys()}
for a, b in pair_list:
    if hit_bool.get(a, False) and hit_bool.get(b, False):
        pair_counts[(a, b)] += 1

n = len(canonical_rows)

dim_out_path = "dimension_hits.csv"
with open(dim_out_path, "w", newline="", encoding="utf-8") as f:
    w = csv.writer(f)
    w.writerow(["dimension", "papers", "share", "mentions"])
    dims_sorted = sorted(dim_cfg.keys(), key=lambda d: (dim_papers[d],
        dim_mentions[d], d), reverse=True)
    for d in dims_sorted:
        papers = dim_papers[d]
        share = (papers / n) if n else 0.0
        w.writerow([d, papers, f"{share:.6f}", dim_mentions[d]])

pair_out_path = "pair_hits.csv"
with open(pair_out_path, "w", newline="", encoding="utf-8") as f:
    w = csv.writer(f)
    w.writerow(["pair", "papers", "share"])
    pairs_sorted = sorted(pair_list, key=lambda p: (pair_counts[p], p[0] + "
        +" + p[1]), reverse=True)
    for a, b in pairs_sorted:
        papers = pair_counts[(a, b)]
        share = (papers / n) if n else 0.0
        w.writerow([f"{a}+{b}", papers, f"{share:.6f}"])

def _top_dims(k: int = 8) -> List[Tuple[str, int, float]]:
    dims_sorted2 = sorted(dim_cfg.keys(), key=lambda d: (dim_papers[d],
        dim_mentions[d], d), reverse=True)
    out = []
    for d in dims_sorted2[:k]:
        papers = dim_papers[d]
        share = (papers / n) if n else 0.0
        out.append((d, papers, share))
    return out

def _top_pairs(k: int = 8) -> List[Tuple[str, int, float]]:
    pairs_sorted2 = sorted(pair_list, key=lambda p: (pair_counts[p], p[0] +

```

```

        "+" + p[1]), reverse=True)
    out = []
    for a, b in pairs_sorted2[:k]:
        papers = pair_counts[(a, b)]
        share = (papers / n) if n else 0.0
        out.append((f"{a}+{b}", papers, share))
    return out

    print("run:", run_ts)
    print("script_version:", SCRIPT_VERSION)
    print("input_jsonl:", os.path.basename(input_path))
    print("total_rows:", total_rows)
    print("unique_papers:", n)
    print("duplicates_dropped:", duplicates)
    print("outputs:")
    print(" canonical_papers.csv")
    print(" dimension_hits.csv")
    print(" pair_hits.csv")
    print("top_dimensions:")
    for d, papers, share in _top_dims(10):
        print(f" {d}: papers={papers}, share={share:.4f}")
    print("top_pairs:")
    for p, papers, share in _top_pairs(10):
        print(f" {p}: papers={papers}, share={share:.4f}")

    return 0

if __name__ == "__main__":
    raise SystemExit(main())

```

Appendix B, Example blockchain anchored record

```

rownum=6690 row=published_utc=2026-02-06T16:48:34Z,ingestion_time
=2026-02-09T14:01:58.469718Z,linenumber_jsonl=6333,url_abs=https://
arxiv.org/abs/2602.06860v1,url_pdf=https://arxiv.org/pdf/2602.06860
v1,hash_of_jsonl=
e626d9ce99ac7e46d85920de9fae2c49e69658eca288f93f07e6a8ce7ce293d7

```

This record illustrates how individual lines of the JSONL archive are anchored on chain so that the dataset can later be verified against the public transaction history.

Appendix C, Raw analysis script output

The following block contains the direct console output produced by the epoch 1 analysis script. The content is included verbatim in order to preserve the exact numerical state from which the tables and statements in this report were derived.

```
python3 arxiv_analyse.py
```

```
run: 2026-02-21T21:20:55Z
script_version: epoch1_kiss_1.0
input_jsonl: arxiv_19022026.jsonl
total_rows: 6690
unique_papers: 6690
duplicates_dropped: 0
outputs:
canonical_papers.csv
dimension_hits.csv
pair_hits.csv

top_dimensions:
privacy: papers=5984, share=0.8945
cloud_computing: papers=253, share=0.0378
rtx_4090: papers=59, share=0.0088
nvidia_rtx: papers=59, share=0.0088
billing: papers=49, share=0.0073
quota: papers=46, share=0.0069
self_hosted: papers=29, share=0.0043
local_llm: papers=25, share=0.0037
run_locally: papers=23, share=0.0034
vendor_lock: papers=19, share=0.0028

top_pairs:
self_hosted+privacy: papers=9, share=0.0013
cloud_gpu+privacy: papers=2, share=0.0003
on_prem_gpu+privacy: papers=1, share=0.0001
local_llm+offline_inference: papers=0, share=0.0000
cloud_gpu+vendor_lock: papers=0, share=0.0000
cloud_gpu+quota: papers=0, share=0.0000
cloud_gpu+egress_fees: papers=0, share=0.0000
cloud_gpu+billing: papers=0, share=0.0000
```